

Product Information Sheet



SOLITAIRE

Sealer Finish



Product

- ✓ Provides a tough, semi-gloss, UV stable finish
- ✓ Suitable for all indoor concrete, stone, terrazzo, glazed and unglazed tiles and pavers
- ✓ Extremely low transfer from tyres
- ✓ Suitable for single applications – no base coat required



One step, super tough base sealer that provides protection to all types of concrete, stone, terrazzo, glazed and unglazed tiles and pavers. Recoats easily and hard wearing.

Technical

Colour	White
Odour	Polymer odour
pH	8.00 – 9.00

Product Code	Outer Pack	APN
CHRC-573015A (5L)	3	9324828002727
CHRC-573015 (15L)	1	9324828002734

Application

Task	Method
Preparation	<ol style="list-style-type: none">1. Sweep or dust mop to remove loose debris or grit.2. Ensure surface is free from oily greasy soil and any old coatings have been removed. To remove oily greasy soil use CROSSFIRE followed by rinsing thoroughly with water. To remove any old acrylic water based coatings use MELTDOWN. (Follow product label instructions.)
Finish application	<ol style="list-style-type: none">1. Apply 2 - 5 coats of SOLITAIRE using an Oates poly-cotton mop, lambs-wool applicator brush or a nylon polish spreader.2. Allow at least 30-45 minutes between coats or until it is completely dry.
Maintenance	<ol style="list-style-type: none">1. A good floor maintenance program will extend the life of your floor finish and extend the time between stripping and resealing.2. Dust mop daily to remove sand and grit tracked over the floor, and where possible use carpet matting in entrance ways.3. Mop or auto scrub daily using SUPASTAR as directed. Spray buff using SHINER. Use an Oates Floormaster Tan pad under standard speed polish or Oates Floormaster Pro-Burnish Lite pad under UHS machinery.
Coverage (m ² /Lt)	Steel trowelled smooth concrete, terrazzo, pavers and unglazed tiles 20 – 30: 1 st coat 30 – 40: 2 nd and all subsequent coats Wood floated or exfoliated surfaces 15 – 20: 1 st coat 20 – 30: 2 nd and all subsequent coats

Version: 1 Page 1 of 1

Research Products recommends you obtain and read the Safety Data Sheet (SDS) before using any product
This Product Information Sheet is offered without guarantee as the conditions and method of application of this product are beyond our control.



Steammaster Pty Ltd


6 Reservoir Avenue, Greenacre SYDNEY NSW 2190 Australia

Tel: 1300 855 677 | Tel: +61 2 9796 3433 | Fax: +61 2 9796 3395

Email: sales@steammaster.com.au | Website: www.steammaster.com.au

SOLITAIRE

Sealer Finish



Hazard Statement

H316: Causes mild skin irritation.

Prevention

P102: Keep out of reach of children.

P264: Wash affected areas thoroughly after handling.

P280: Wear protective gloves, protective clothing and eye or face protection.